



# OCEANO 2.0

OCEANO 2.0 2W AL-AL 60° 4000K 24V  
HC 10M

Cod: **CEA02FCL100M00**



#### IdroSkud® protection system

- polarity reversal protection
- voltage spikes protection
- water infiltration protection



#### Protection class III

Designed to be supplied from a separated extra-low voltage (SELV) power supply



#### IP 66

Protected against powerful power jets, 100 liters per minute



#### IP 68

Protected against continuous immersion up to 3 meters



#### IK 07

Protected against impact of 2 J



#### High temperatures

Design to withstand temperatures up to +50° C



#### Walk-over

Fixture design to withstand a static load up to 5 kN



#### C5 - Very high

corrosion resistance level ISO 9223



#### Mizar warranty

5 years warranty



## Technical description

Inground luminaire, walk-over, suitable for outdoor environments (IP66/IP68), with operating temperature range: -20°C / +50°C. To provide maximum versatility of application, the body can be made of aluminum or steel; the frame, aluminum, steel or brass. The light source consists of a single 2W power Led chip powered at 24V constant voltage with integrated driver. The luminous flux makes it ideal for tracing pedestrian paths or achieving a starry ceiling effect, thanks to the different emission angles. The source is set back for greater visual comfort. Color rendering index CRI > 90. Oceano is equipped with IdroSkud® system to protect electronic components from voltage spikes, polarity reversal and water infiltration. There are optionals for anti-glare (honeycomb) and installation accessories (draining and waterproof outercase and spring for ceiling attachment). The product must be combined with a power supply to ensure its operation. The power supply must be ordered separately. The amount of luminaires that can be connected to a single power supply varies depending on the type of installation. It is up to the installer to verify the possible voltage drop by evaluating the distance between the product and the power supply.

## Lighting data

|                             |                       |
|-----------------------------|-----------------------|
| Source type                 | single chip power LED |
| CCT                         | 4000K                 |
| CRI                         | > 90                  |
| MacAdam (SDCM)              | 2                     |
| Source lumen output (lm)    | 157                   |
| Luminaire lumen output (lm) | 95                    |
| Light emission              | Wide                  |
| Beam angle                  | 60°                   |

|                      |                                                                                  |
|----------------------|----------------------------------------------------------------------------------|
| Photobiological risk | RG0                                                                              |
| ULR                  | 100.00%                                                                          |
| BUG Rating           | B0 U3 G0                                                                         |
| CIE Flux Code        | 0 0 0 0 100                                                                      |
| LED lifetime         | L80 B10 50.000h                                                                  |
| Efficiency class     | This product contains a light source of energy efficiency class (EU2019/2015): F |

## Mechanical data

|                          |                                                                                |
|--------------------------|--------------------------------------------------------------------------------|
| Diameter (mm)            | 40                                                                             |
| Height (mm)              | 76                                                                             |
| Weight (g)               | 101                                                                            |
| IP Rating                | IP66 / IP68                                                                    |
| IK rating                | IK07                                                                           |
| Shape                    | Round                                                                          |
| Finishing colour         | Aluminium / Aluminium                                                          |
| Frame material           | Anodized 20u aluminum anticorodal 6082, Anodized 20u aluminum anticorodal 6082 |
| Body material            | Anodized 20u aluminum anticorodal 6082                                         |
| External screws material | Stainless steel 316L (A4)                                                      |
| Diffuser material        | Extraclear tempered glass                                                      |


|                             |                        |
|-----------------------------|------------------------|
| Diffuser thickness (mm)     | 6                      |
| Class ISO 9223              | C5                     |
| Optic type                  | Technopolymer TIR Lens |
| Optical optional            | Honeycomb              |
| Maximal working temperature | +50° C                 |
| Minimal working temperature | -20° C                 |
| Maximal static load (kN)    | 5                      |
| Walk-over                   | Yes                    |
| Driver-over                 | No                     |
| Maximal surface temperature | +50° C                 |
| Areas EN 60598-2-13         | A1 / A2                |

## Electrical data

|                                 |                                  |
|---------------------------------|----------------------------------|
| Nominal power (W)               | 2                                |
| Power supply (input power type) | Costant voltage - 24V            |
| Ballast                         | Remote                           |
| Insulation class                | III                              |
| Dimmable                        | Yes                              |
| Power cable type                | H05RN - F 2x0,75 mm <sup>2</sup> |
| Power cable length              | 10 m (verify voltage drop)       |

|                             |                     |
|-----------------------------|---------------------|
| Electrical connection       | Parallel connection |
| Idroskud® protection        | Yes                 |
| Inverse polarity protection | Yes                 |
| Voltage spikes protection   | Yes                 |

## Photometry



## Technical drawing



## Accessories



### DRAINING OUTERCASE

Outercase draining OCEANO 2

Cod: CEAZZ003



### SLIM DRAINING OUTERCASE

Outercase draining slim OCEANO 2

Cod: CEAZZ004



### SLIM WATER-PROOF OUTERCASE

Outercase waterproof slim OCEANO 2

Cod: CEAZZ005



### SPRING FOR CEILING MOUNTING

Spring for ceiling mounting OCEANO 2

Cod: CEAZZ015



### NOT DIMMABLE POWER SUPPLY

Power supply DC 24V 14,4W IP67  
ON/OFF

Cod: MID0019



### NOT DIMMABLE POWER SUPPLY

Power supply DC 24V 36W IP67 ON/OFF

Cod: MID0020



### DIMMABLE POWER SUPPLY

Power supply 220/240 50/60Hz 24V  
24W IP67 DALI

Cod: MID0021