

# OCEANO 3.3

## DRIVE-OVER

OCEANO 3.3 3W ST-ST 10° 2700K 24V HC 10M

Cod: **CEA07CCS101M00**



IdroSkud® protection system  
- polarity reversal protection  
- voltage spikes protection  
- water infiltration protection



Protection class III  
Designed to be supplied from a separated extra-low voltage (SELV) power supply



IP 68 up to 10m  
Protected against continuous immersion up to 10 meters



IP 66  
Protected against powerful power jets, 100 liters per minute



IK 10  
Protected against impact of 20 J



High temperatures  
Design to withstand temperatures up to +50° C



Drive-over  
Fixture design to withstand a static load up to 20 kN



CX - Extreme  
corrosion resistance level ISO 9223



Mizar warranty  
5 years warranty



### Technical description

Inground luminaire, drive-over, suitable for outdoor and underwater environments up to 10 m (IP66/IP68), with operating temperature range: -20°C / +50°C. To provide maximum versatility of application, the body can be made of aluminum or steel; the frame, aluminum or steel. The light source consists of a single 3W power Led chip powered at 24V constant voltage with integrated driver. The luminous flux makes it ideal for marking pedestrian paths or illuminating architectural details. The source is recessed for greater visual comfort. Color rendering index CRI > 90. Oceano is equipped with IdroSkud® system to protect electronic components from voltage spikes, polarity reversal and water infiltration. There are options for anti-glare (honeycomb and louvre) and installation accessories (drive-over outer case). The product must be combined with a power supply to ensure its operation. The power supply must be ordered separately. The amount of luminaires that can be connected to a single power supply varies depending on the type of installation. It is up to the installer to verify the possible voltage drop by evaluating the distance between the product and the power supply.

## Lighting data

|                             |                       |                      |                                                                                  |
|-----------------------------|-----------------------|----------------------|----------------------------------------------------------------------------------|
| Source type                 | single chip power LED | Photobiological risk | RG0                                                                              |
| CCT                         | 2700K                 | ULR                  | 100.00%                                                                          |
| CRI                         | > 90                  | BUG Rating           | B0 U3 G0                                                                         |
| MacAdam (SDCM)              | 2                     | CIE Flux Code        | 0 0 0 0 100                                                                      |
| Source lumen output (lm)    | 236                   | LED lifetime         | L80 B10 50.000h                                                                  |
| Luminaire lumen output (lm) | 136                   | Efficiency class     | This product contains a light source of energy efficiency class (EU2019/2015): F |
| Light emission              | Narrow                |                      |                                                                                  |
| Beam angle                  | 10°                   |                      |                                                                                  |


## Mechanical data

|                          |                           |                             |                        |
|--------------------------|---------------------------|-----------------------------|------------------------|
| Width (mm)               | 90                        | Diffuser thickness (mm)     | 8                      |
| Length (mm)              | 90                        | Class ISO 9223              | CX                     |
| Height (mm)              | 93                        | Optic type                  | Technopolymer TIR Lens |
| Weight (Kg)              | 0.757                     | Optical optional            | Honeycomb              |
| IP Rating                | IP66 / IP68 10m           | Maximal working temperature | +50° C                 |
| IK rating                | IK10                      | Minimal working temperature | -20° C                 |
| Shape                    | Square                    | Maximum static load (kg)    | 2000                   |
| Finishing colour         | Steel / Steel             | Walk-over                   | Yes                    |
| Frame material           | Stainless steel 316L      | Drive-over                  | Yes                    |
| Body material            | Stainless steel 316L      | Maximal surface temperature | +50° C                 |
| External screws material | Stainless steel 316L (A4) | Areas EN 60598-2-13         | A1 / A2 / A3 / A4      |
| Diffuser material        | Extraclear tempered glass |                             |                        |


## Electrical data

|                                 |                                  |                             |                     |
|---------------------------------|----------------------------------|-----------------------------|---------------------|
| Nominal power (W)               | 3                                | Electrical connection       | Parallel connection |
| Power supply (input power type) | Costant voltage - 24V            | Idroskud® protection        | Yes                 |
| Ballast                         | Remote                           | Inverse polarity protection | Yes                 |
| Insulation class                | III                              | Voltage spikes protection   | Yes                 |
| Dimmable                        | Yes (PWM)                        |                             |                     |
| Power cable type                | H05RN - F 2x0,75 mm <sup>2</sup> |                             |                     |
| Power cable length              | 10 m (verify voltage drop)       |                             |                     |

## Photometry



## Technical drawing



## Accessories



### DIMMABLE POWER SUPPLY

Power supply 220/240 50/60Hz 24V  
24W IP67 DALI

Cod: MID0021

### NOT DIMMABLE POWER SUPPLY

Power supply DC 24V 14,4W IP67  
ON/OFF

Cod: MID0019

### NOT DIMMABLE POWER SUPPLY

Power supply DC 24V 36W IP67 ON/OFF

Cod: MID0020

### DRIVE-OVER OUTERCASE

Outercase drive-over OCEANO 3

Cod: CEAZZ009

