



# EGEO 1.0

EGEO 1.0 1W AL 25° 2700K 24V 0,4M

Cod: **CEA12CCM000A00**



#### IdroSkud® protection system

- polarity reversal protection
- voltage spikes protection
- water infiltration protection



#### Protection class III

Designed to be supplied from a separated extra-low voltage (SELV) power supply



#### IP 66

Protected against powerful power jets, 100 liters per minute



#### IP 68

Protected against continuous immersion up to 3 meters



#### IK 09

Protected against impact of 10 J



#### High temperatures

Design to withstand temperatures up to +50° C



#### C5 - Very high

corrosion resistance level ISO 9223



#### Mizar warranty

5 years warranty



## Technical description

Floodlight suitable for outdoor environments (IP66/IP68) with operating temperature range: -20°C / +50°C. To offer maximum versatility of application, the body can be made of aluminum or steel; the bracket, made of steel for both models, allows the fixture's tilt to be adjusted. The light source consists of a single 1W power Led chip powered at 24V constant voltage with integrated driver. The luminous flux makes it ideal for illuminating architectural details, garden plants or water features, thanks to the different emission angles. The source is set back for greater visual comfort. Color rendering index CRI > 90. EGEO is equipped with IdroSkud® system to protect electronic components from voltage spikes, polarity reversal and water infiltration. An accessory for installation in the ground (stake) is provided. The product must be combined with a power supply to ensure its operation. The power supply must be ordered separately. The amount of luminaires that can be connected to a single power supply varies depending on the type of installation. It is up to the installer to verify the possible voltage drop by evaluating the distance between the product and the power supply.

## Lighting data

|                             |                       |                      |                                                                                  |
|-----------------------------|-----------------------|----------------------|----------------------------------------------------------------------------------|
| Source type                 | single chip power LED | Photobiological risk | RG0                                                                              |
| CCT                         | 2700K                 | ULR                  | 0.00%                                                                            |
| CRI                         | > 90                  | BUG Rating           | B0 U0 G0                                                                         |
| MacAdam (SDCM)              | 2                     | CIE Flux Code        | 83 93 98 100 100                                                                 |
| Source lumen output (lm)    | 126                   | LED lifetime         | L80 B10 50.000h                                                                  |
| Luminaire lumen output (lm) | 64                    | Efficiency class     | This product contains a light source of energy efficiency class (EU2019/2015): E |
| Light emission              | Medium                |                      |                                                                                  |
| Beam angle                  | 25°                   |                      |                                                                                  |

## Mechanical data

|                  |                                        |                             |                           |
|------------------|----------------------------------------|-----------------------------|---------------------------|
| Width (mm)       | 27                                     | External screws material    | Stainless steel 316L (A4) |
| Length (mm)      | 44                                     | Diffuser material           | Extraclear tempered glass |
| Height (mm)      | 46.5                                   | Diffuser thickness (mm)     | 4                         |
| Weight (g)       | 52                                     | Class ISO 9223              | C5                        |
| IP Rating        | IP66 / IP68                            | Optic type                  | Technopolymer TIR Lens    |
| IK rating        | IK09                                   | Optical optional            | None                      |
| Finishing colour | Aluminium / Aluminium                  | Maximal working temperature | +50° C                    |
| Frame material   | Anodized 20u aluminum anticorodal 6082 | Minimal working temperature | -20° C                    |
| Body material    | Anodized 20u aluminum anticorodal 6082 |                             |                           |

## Electrical data

|                                 |                          |                             |                     |
|---------------------------------|--------------------------|-----------------------------|---------------------|
| Nominal power (W)               | 1                        | Electrical connection       | Parallel connection |
| Power supply (input power type) | Costant voltage - 24V    | Idroskud® protection        | Yes                 |
| Ballast                         | Remote                   | Inverse polarity protection | Yes                 |
| Insulation class                | III                      | Voltage spikes protection   | Yes                 |
| Dimmable                        | Yes                      |                             |                     |
| Power cable type                | FR5FOEM7 - AD8 2x0,5 mm² |                             |                     |
| Power cable length              | 0,4 m                    |                             |                     |

## Photometry



## Technical drawing



## Accessories



### GROUND STAKE

Stake for floodlight - small size

Cod: CEAZZZ016



### NOT DIMMABLE POWER SUPPLY

Power supply DC 24V 14,4W IP67  
ON/OFF

Cod: MID0019



### NOT DIMMABLE POWER SUPPLY

Power supply DC 24V 36W IP67 ON/OFF

Cod: MID0020



### DIMMABLE POWER SUPPLY

Power supply 220/240 50/60Hz 24V  
24W IP67 DALI

Cod: MID0021