



QUANTUM 2.2

QUANTUM 2.2 14W AN7016 60° 4000K
220V DALI

Cod: **QUA03FCL0G0Z01**



Protection class II
Double insulated electrical appliance



IP 65
Protected against water jets



IK 06
Protected against impact of 1 J



High temperatures
Design to withstand temperatures up to +50° C



C5 - Very high
corrosion resistance level ISO 9223



DALI
Luminaire with dimmable power-supply integrated



Mizar warranty
5 years warranty



Technical description

Double-emission fixture for wall mounting, suitable for outdoor environments (IP65), with wide operating temperature range: -20°C / +50°C. The body is made of die-cast aluminum protected by polyester epoxy paint to ensure corrosion resistance of 1500 hours in salt spray. The light source is a single 14W Power Led chip powered by 220Vac (integrated power supply). The luminous flux and distinctive design make it ideal for illuminating facades and architectural details. Color rendering index CRI > 90. Optional anti-glare (honeycomb) is provided.

Lighting data

Source type	double chip power LED	Photobiological risk	RG0
CCT	4000K	ULR	50.00%
CRI	> 90	BUG Rating	B1 U3 G0
MacAdam (SDCM)	3	CIE Flux Code	73 91 98 50 100
Source lumen output (lm)	890	LED lifetime	L80 B10 50.000h
Luminaire lumen output (lm)	703	Efficiency class	This product contains a light source of energy efficiency class (EU2019/2015): G
Light emission	Wide		
Beam angle	60°		

Mechanical data

Width (mm)	78	Body material	Die-cast aluminum EN AB46100
Length (mm)	112	Diffuser material	Extraclear tempered glass
Height (mm)	235	Diffuser thickness (mm)	6
Weight (g)	1660	Class ISO 9223	C5
IP Rating	IP65	Optic type	Technopolymer TIR Lens
IK rating	IK06	Optical optional	None
Type of finishing	Protective primer followed by epoxy and polyester paint	Maximal working temperature	+50° C
Finishing colour	Anthracite RAL7016	Minimal working temperature	-20° C

Electrical data

Nominal power (W)	14	Connector type	Class II terminal block
Power supply (input power type)	220V AC 50/60 Hz	Power cable length	Not pre-wired
Ballast	Integrated		
Insulation class	II		
Dimmable	Yes (DALI)		

Photometry



Technical drawing

