



QUANTUM TIGE 1.0

QUANTUM TIGE 1.0 300mm 3W
WH9003 25° 3000K 220V HC

Cod: **QUA09DCM1W0Z00**



Protection class II
Double insulated electrical appliance



IP 65
Protected against water jets



IK 06
Protected against impact of 1 J



High temperatures
Design to withstand temperatures up to +50° C



C5 - Very high
corrosion resistance level ISO 9223



Mizar warranty
5 years warranty



Technical description

Luminaire for ceiling mounting with rigid suspension ("tige"), suitable for outdoor environments (IP65), with wide operating temperature range: -20°C / +50°C. The extruded aluminium tige can be of different lengths and customised on request. The body is made of die-cast aluminium protected by polyester epoxy paint to ensure corrosion resistance of 1500 hours in salt spray. The light source is a single 3W Power Led chip powered by 220Vac (integrated power supply). The luminous flux and distinctive design make it ideal for illuminating terraces or walkways under porches. Color rendering index CRI > 90. Optional anti-glare (honeycomb) is provided.

Lighting data

Source type	single chip power LED	Photobiological risk	RG0
CCT	3000K	ULR	0.00%
CRI	> 90	BUG Rating	B0 U1 G0
MacAdam (SDCM)	3	CIE Flux Code	96 98 99 100 100
Source lumen output (lm)	236	LED lifetime	L80 B10 50.000h
Luminaire lumen output (lm)	153	Efficiency class	This product contains a light source of energy efficiency class (EU2019/2015): F
Light emission	Medium		
Beam angle	25°		


Mechanical data

Diameter (mm)	54	Diffuser material	Extraclear tempered glass
Height (mm)	300	Diffuser thickness (mm)	5
Weight (g)	370	Class ISO 9223	C5
IP Rating	IP65	Optic type	Technopolymer TIR Lens
IK rating	IK06	Optical optional	Honeycomb
Type of finishing	Protective primer followed by epoxy and polyester paint	Maximal working temperature	+50° C
Finishing colour	White RAL9003	Minimal working temperature	-20° C
Body material	Die-cast aluminum EN AB46100		

Electrical data

Nominal power (W)	3	Connector type	Class II terminal block
Power supply (input power type)	220V AC 50/60 Hz	Power cable length	Not pre-wired
Ballast	Integrated		
Insulation class	II		
Dimmable	No		

Photometry



Technical drawing

