

we suggest to use our online tool to verify the voltage drop / link: www.mizar.it/en/voltage-drop-check/
 suggeriamo di utilizzare lo strumento online per verificare la caduta di tensione / link: www.mizar.it/it/verifico-caduta-di-tensione/

Product code Codice prodotto	Description Descrizione	Type Tipo	Voltage out Tensione	Power (W) Potenza	Current out Corrente	IP degree Grado IP	MIZAR products Prodotti MIZAR	Quantity quantità	Notes Note
MID0031	POWER SUPPLY 24V 200W Max 8A IP67 DALI2	Costant voltage Tensione costante	24V	200W	8A	67	ACUS 1.3 RGBW	12	DALI2/PWM
							ELIOS 1.1 RGBW	12	
							FLUMEN 3.0 10W	16	
							FLUMEN 3.0 14W	11	
							FLUMEN 3.1 RGBW 13W	11	
							LINEO 1.0 (510 mm)	26	
							LINEO 1.1 (1010 mm)	13	
							LINEO 1.2 (1510 mm)	8	
							LINEO 2.0 RGBW (510 mm)	13	
							LINEO 2.1 RGBW (1010 mm)	6	
							LINEO 2.2 RGBW (1510 mm)	4	
							OCEANO 4.0 / 4.1 RGBW	18	
EGEO 4.1 RGBW	18								
Power supplies costant voltage 48V (for parallel connection) Alimentatori a tensione costante 48V (per connessioni in parallelo)									
MID0032	POWER SUPPLY DC 48V 100W 2,1A IP 67 DALI2/PWM	Costant voltage Tensione costante	48V	100W	2,1A	67	ELIOS 1.0	4	DALI2/PWM
MID0033	POWER SUPPLY DC 48V 160W 3,34A IP 67 DALI2/PWM	Costant voltage Tensione costante	48V	160W	3,34A	67	ELIOS 1.0	6	DALI2/PWM
Power supplies costant current (for series connection) Alimentatori a corrente costante (per connessioni in serie)									
MID0022	POWER SUPPLY 44V 700mA	Costant current Corrente costante	5-44V	30	700mA dc	20	ACUS 1.0 ACUS 1.1 ACUS 1.2 ACUS 2.0	1 1 2 2	
MID0024	POWER SUPPLY 5-44V 350-700mA	Costant current Corrente costante	25-85V	15/70W	350-700mA	20	ACUS 1.0 ACUS 1.1	2 2	solo per ACUS 1.0 e 1.1 only for ACUS 1.0 and 1.1
MID0025	POWER SUPPLY 10-54V 150-1050mA DALI/NFC	Costant current Corrente costante	10-54V	1,5/38W	150-1050mA	20	ACUS 1.0 ACUS 1.1 ACUS 1.2 ACUS 2.0	1 1 2 2	DALI-NFC
MID0026	POWER SUPPLY 10-50V 700mA IP68	Costant current Corrente costante	10-50V	15-70W	700mA	68	ACUS 1.0 ACUS 1.1 ACUS 1.2 ACUS 2.0	1 1 2 2	
MID0027	POWER SUPPLY 2-49V 250-700mA IP68 DALI	Costant current Corrente costante	2-49V	1/30W	250-700mA	68	ACUS 1.0 ACUS 1.1 ACUS 1.2 ACUS 2.0	1 1 2 2	DALI
PWM controllers (RGBW) controller PWM RGBW									
MID0023	CONTROLLER RGBW PWM/WIFI	Controller PWM	5x 12-24V	5x 36-72W	5x 3A	20	ACUS 1.3 RGBW ELIOS 1.1 RGBW FLUMEN 3.1 RGBW LINEO 2.0 RGBW (510 mm) LINEO 2.1 RGBW (1010 mm) LINEO 2.2 RGBW (1510 mm) OCEANO 4.0 / 4.1 RGBW EGEO 4.1 RGBW	depending on power supply model dipende dall'alimentatore scelto	5 channels 5 canali