

LINEO 1.2

LINEO 1.2 1510mm 18W OPAL 2700K 24V

Cod: **LNE02CBK000A00**

**IdroSkud® protection system**

- polarity reversal protection
- voltage spikes protection
- water infiltration protection

**Protection class III**

Designed to be supplied from a separated extra-low voltage (SELV) power supply

**IP 66**

Protected against powerful power jets, 100 liters per minute

**IP 67**

Protected against temporary immersion (30 minutes) up to 1 meter

**IK 10**

Protected against impact of 20 J

**High temperatures**

Design to withstand temperatures up to +50° C

**Driver-over**

Fixture design to withstand a static load up to 20 kN

**CX - Extreme**

corrosion resistance level ISO 9223

**Mizar warranty**

5 years warranty



Technical description

Linear in-ground luminaire, drive-over, suitable for outdoor environments (IP66/IP67), with operating temperature range: -20°C / +50°C. The body is made of PMMA, transparent and opal on the upper side; the endcaps are made of 316L stainless steel. The light source is LED SMD3014, powered at 24V with built-in driver. The luminous flux makes it ideal for marking pedestrian and driveway paths, or creating light cuts on floors, walls and ceilings. Color rendering index CRI > 80. Lineo is equipped with IdroSkud® system to protect electronic components from voltage spikes, polarity reversal and water infiltration. Installation accessories are provided (floor and plasterboard outercase; cable extensions up to 15 m). The product must be combined with a power supply to ensure its operation. The power supply must be ordered separately. The amount of luminaires that can be connected to a single power supply varies depending on the type of installation. It is up to the installer to verify the possible voltage drop by evaluating the distance between the product and the power supply.

Lighting data

Source type	SMD chip 3014	Photobiological risk	RG0
CCT	2700K	ULR	100.00%
CRI	> 80	BUG Rating	B0 U3 G0
MacAdam (SDCM)	3	CIE Flux Code	0 0 0 0 100
Source lumen output (lm)	1824	LED lifetime	L80 B10 50.000h
Luminaire lumen output (lm)	438	Efficiency class	This product contains a light source of energy efficiency class (EU2019/2015): F
Light emission	Diffused		
Beam angle	120°		


Mechanical data

Width (mm)	27	Class ISO 9223	CX
Length (mm)	1510	Optical optional	None
Height (mm)	49	Maximal working temperature	+50° C
Weight (g)	1470	Minimal working temperature	-20° C
IP Rating	IP66 / IP67	Maximal static load (kN)	20
IK rating	IK10	Walk-over	Yes
Finishing colour	Opal white	Driver-over	Yes
Frame material	Stainless steel 316L	Maximal surface temperature	+50° C
Body material	Transparent PMMA	Areas EN 60598-2-13	A1 / A2 / A3 / A4
Diffuser material	Opal PMMA		


Electrical data

Nominal power (W)	18	Electrical connection	Parallel connection
Power supply (input power type)	Costant voltage - 24V	Idroskud® protection	Yes
Ballast	Remote	Inverse polarity protection	Yes
Insulation class	III	Voltage spikes protection	Yes
Dimmable	Yes		
Connector type	M12 - 5 poles IP67		
Power cable length	0,4 m		


Photometry




Technical drawing



Accessories



FLOOR OUTERCASE 1511 MM
Outercase PC for floor 1511mm LINEO
Cod: LNEZZZ002



PLASTER OUTERCASE 1511 MM
Outercase PC for plasterboard 1511mm LINEO
Cod: LNEZZZ005



EXTENSION 0,5 M
5-pole extension 0.5m OT/NI rings for LINEO
Cod: LNEZZZ012



EXTENSION 1 M
5-pole extension 1m OT/NI rings for LINEO
Cod: LNEZZZ013



EXTENSION 1,5 M
5-pole extension 1.5m OT/NI rings for LINEO
Cod: LNEZZZ014




EXTENSION 5 M
5-pole extension 5m OT/NI rings for LINEO
Cod: LNEZZZ015



EXTENSION 10 M
5-pole extension 10m OT/NI rings for LINEO
Cod: LNEZZZ016




EXTENSION 15 M
5-pole extension 15m OT/NI rings for LINEO
Cod: LNEZZZ017



SPLITTER 2 WAY

2-way 5-pole splitter with OT/NI rings for
LINEO

Cod: LNEZZZ019



POWER CABLE

Power cable 5 poles - M12 female 1,5m

Cod: LNEZZZ021



OUTERCASE HEAD KIT

Head kit for ground LINEO outercase

Cod: LNEZZZ022



PLASTER OUTERCASE HEAD KIT

Head kit for plasterboard LINEO
outercase

Cod: LNEZZZ023



OUTERCASE FIXING KIT

Fixing kit for LINEO outercase

Cod: LNEZZZ024



OUTERCASE COUPLING KIT

Bracket kit for coupling LINEO
outercase

Cod: LNEZZZ025



EXTRACTION KIT

Extraction kit from outercase for LINEO

Cod: LNEZZZ026



NOT DIMMABLE POWER SUPPLY

Power supply DC 24V 70W 2,9A IP67

Cod: MID0028



NOT DIMMABLE POWER SUPPLY

Power supply DC 24V 150W 6,25A IP67

Cod: MID0029



DIMMABLE POWER SUPPLY

Power supply DC 24V 120W 5A IP67
DALI2/PWM

Cod: MID0030



DIMMABLE POWER SUPPLY

Power supply DC 24V 200W 5A IP67
DALI2/PWM

Cod: MID0031