

QUANTUM FLOOD

1.0

QUANTUM FLOOD 1.0 3W PRIMER 25°
4000K 220V HC

Cod: **QUA07FCM1PRZ00**

**Protection class II**

Double insulated electrical appliance

**IP 65**

Protected against water jets

**IK 06**

Protected against impact of 1 J

**High temperatures**

Design to withstand temperatures up to +50°C

**C5 - Very high**


corrosion resistance level ISO 9223

**Customizable finishing**

The luminaire could be painted by final client

**Mizar warranty**

5 years warranty



Technical description

Floodlight suitable for outdoor environments (IP65), with operating temperature range: -20°C / +50°C. To reduce weight and ensure corrosion resistance, the body is made of aluminum. The aluminum body is protected by polyester epoxy paint to ensure corrosion resistance of 1500 hours in salt spray. The light source is a single Power LED chip, for maximum power of 3W. The product has an integrated 220 Vac power supply. The luminaire is ideal for marking pedestrian paths or illuminating facades and architectural details thanks to the optics with TIR lens. The LED source is recessed for greater visual comfort. Color rendering index CRI > 90. There are optionals for anti-glare (honeycomb) and accessory for installation in the ground (stake).

Lighting data

| | | | |
|-----------------------------|-----------------------|----------------------|--|
| Source type | single chip power LED | Photobiological risk | RG0 |
| CCT | 4000K | ULR | 0.00% |
| CRI | > 90 | BUG Rating | B0 U1 G0 |
| MacAdam (SDCM) | 3 | CIE Flux Code | 96 98 99 100 100 |
| Source lumen output (lm) | 236 | LED lifetime | L80 B10 50.000h |
| Luminaire lumen output (lm) | 160 | Efficiency class | This product contains a light source of energy efficiency class (EU2019/2015): F |
| Light emission | Medium | | |
| Beam angle | 25° | | |

Mechanical data

| | | | |
|-------------------|-----------------------------|-----------------------------|------------------------------|
| Width (mm) | 54 | Body material | Die-cast aluminum EN AB46100 |
| Length (mm) | 119 | Diffuser material | Extraclear tempered glass |
| Height (mm) | 123 | Diffuser thickness (mm) | 5 |
| Weight (g) | 550 | Class ISO 9223 | C5 |
| IP Rating | IP66 | Optic type | Technopolymer TIR Lens |
| IK rating | IK06 | Optical optional | Honeycomb |
| Type of finishing | Paintable protective primer | Maximal working temperature | +50° C |
| Finishing colour | Paintable primer | Minimal working temperature | -20° C |

Electrical data

| | | | |
|---------------------------------|------------------|--------------------|-------------------------|
| Nominal power (W) | 3 | Connector type | Class II terminal block |
| Power supply (input power type) | 220V AC 50/60 Hz | Power cable length | Not pre-wired |
| Ballast | Integrated | | |
| Insulation class | II | | |
| Dimmable | No | | |

Photometry



Technical drawing

