

# QUANTUM FLOOD

## 1.0

QUANTUM FLOOD 1.0 3W PRIMER 40°  
4000K 220V

Cod: **QUA07FCL0PRZ00**

**Protection class II**

Double insulated electrical appliance

**IP 65**

Protected against water jets

**IK 06**

Protected against impact of 1 J

**High temperatures**

Design to withstand temperatures up to +50°C

**C5 - Very high**


corrosion resistance level ISO 9223

**Customizable finishing**

The luminaire could be painted by final client

**Mizar warranty**

5 years warranty



### Technical description

Floodlight suitable for outdoor environments (IP65), with operating temperature range: -20°C / +50°C. To reduce weight and ensure corrosion resistance, the body is made of aluminum. The aluminum body is protected by polyester epoxy paint to ensure corrosion resistance of 1500 hours in salt spray. The light source is a single Power LED chip, for maximum power of 3W. The product has an integrated 220 Vac power supply. The luminaire is ideal for marking pedestrian paths or illuminating facades and architectural details thanks to the optics with TIR lens. The LED source is recessed for greater visual comfort. Color rendering index CRI > 90. There are optionals for anti-glare (honeycomb) and accessory for installation in the ground (stake).

## Lighting data

Source type	single chip power LED	Photobiological risk	RG0
CCT	4000K	ULR	0.00%
CRI	> 90	BUG Rating	B0 U0 G0
MacAdam (SDCM)	3	CIE Flux Code	96 99 100 100 100
Source lumen output (lm)	236	LED lifetime	L80 B10 50.000h
Luminaire lumen output (lm)	144	Efficiency class	This product contains a light source of energy efficiency class (EU2019/2015): F
Light emission	Wide		
Beam angle	40°		

## Mechanical data

Width (mm)	54	Body material	Die-cast aluminum EN AB46100
Length (mm)	119	Diffuser material	Extraclear tempered glass
Height (mm)	123	Diffuser thickness (mm)	5
Weight (g)	550	Class ISO 9223	C5
IP Rating	IP66	Optic type	Technopolymer TIR Lens
IK rating	IK06	Optical optional	None
Type of finishing	Paintable protective primer	Maximal working temperature	+50° C
Finishing colour	Paintable primer	Minimal working temperature	-20° C

## Electrical data

Nominal power (W)	3	Connector type	Class II terminal block
Power supply (input power type)	220V AC 50/60 Hz	Power cable length	Not pre-wired
Ballast	Integrated		
Insulation class	II		
Dimmable	No		

## Photometry



## Technical drawing

