



QUANTUM TIGE 2.0

QUANTUM TIGE 2.0 450mm 7W PRIMER
60° 4000K 220V

Cod: **QUA10FCL0PRZ00**



Protection class II
Double insulated electrical appliance



IP 65
Protected against water jets



IK 06
Protected against impact of 1 J



High temperatures
Design to withstand temperatures up to +50° C



C5 - Very high
corrosion resistance level ISO 9223



DALI
Luminaire with dimmable power-supply integrated



Customizable finishing
The luminaire could be painted by final client



Mizar warranty
5 years warranty



Technical description

Luminaire for ceiling mounting with rigid suspension ("tige"), suitable for outdoor environments (IP65), with wide operating temperature range: -20°C / +50°C. The extruded aluminium tige can be of different lengths and customised on request. The body is made of die-cast aluminum protected by polyester epoxy paint to ensure corrosion resistance of 1500 hours in salt spray. The light source is a single 7W Power Led chip powered by 220Vac (integrated power supply). The luminous flux and distinctive design make it ideal for illuminating terraces or walkways under porches. Color rendering index CRI > 90. Optional anti-glare (honeycomb) is provided.

Lighting data

Source type	single chip power LED	Photobiological risk	RG0
CCT	4000K	ULR	0.00%
CRI	> 90	BUG Rating	B0 U1 G0
MacAdam (SDCM)	3	CIE Flux Code	73 91 98 100 100
Source lumen output (lm)	445	LED lifetime	L80 B10 50.000h
Luminaire lumen output (lm)	352	Efficiency class	This product contains a light source of energy efficiency class (EU2019/2015): G
Light emission	Wide		
Beam angle	60°		

Mechanical data

Diameter (mm)	78	Diffuser material	Extraclear tempered glass
Height (mm)	450	Diffuser thickness (mm)	6
Weight (g)	460	Class ISO 9223	C5
IP Rating	IP65	Optic type	Technopolymer TIR Lens
IK rating	IK06	Optical optional	None
Type of finishing	Paintable protective primer	Maximal working temperature	+50° C
Finishing colour	Paintable primer	Minimal working temperature	-20° C
Body material	Die-cast aluminum EN AB46100		

Electrical data

Nominal power (W)	7	Connector type	Class II terminal block
Power supply (input power type)	220V AC 50/60 Hz	Power cable length	Not pre-wired
Ballast	Integrated		
Insulation class	II		
Dimmable	Yes (DALI)		

Photometry



Technical drawing

