



VITRUM 3.0 7W WHITE ELL 3000K 24V

Cod: VIT03DCE202M00



IP 68 Protected against continous immersion up to 3 meters



IP 68

CX - Extreme corrosion resistance level ISO 9223



۵ 🔀 🔘

RoHS

Protection class III Designed to be supplied from a separated extra-low voltage (SELV) power supply



Protected against powerful power jets, 100 liters per minute



DATA SHEET

IK 10 Protected against impact of 20 J

Mizar warranty

5 vears warrantv



Walk-over

Fixture design to withstand a static load up to 5 kN



Fully flush inground luminaire, walk-over , suitable for outdoor and underwater environments (IP66/IP68) with operating temperature range: -20°C / +50°C. Its special feature is that it has a tempered glass screen without metal frame, opal, with black screen-printed edge. The body is made of black anodized anticorodal aluminum. The light source consists of a single 7W power Led chip powered at 24Vdc constant voltage with integrated driver. The minimalist design makes it ideal as a lighting fixture for elegant indoor and outdoor environments, as well as for high-humidity situations (spas, wine cellars). The source is set back for greater visual comfort. Color rendering index CRI > 90. Vitrum is equipped with IdroSkud® system to protect electronic components from voltage spikes, polarity reversal and water infiltration. There are installation accessories (draining, watertight and plasterboard outercase). The product must be combined with a power supply to ensure its operation. The power supply must be ordered separately. The amount of luminaires that can be connected to a single power supply varies depending on the type of installation. It is up to the installer to verify the possible voltage drop by evaluating the distance between the product and the power supply.



Lighting data

Source type	single chip power LED	Photobiological risk	RGO
CCT	3000K	ULR	100.00%
CRI	> 90	BUG Rating	B0 U3 G0
MacAdam (SDCM)	2	CIE Flux Code	0 0 0 0 100
Source lumen output (lm)	445	LED lifetime	L80 B10 50.000h
Luminaire lumen output (lm)	334	Efficiency class	This product contains a light
Light emission	Elliptical		source of energy efficiency
Beam angle	15°x60°		class (EU2019/2015): G

Mechanical data

Diameter (mm)	85	Optic type	Technopolymer TIR Lens
Height (mm)	108	Optical optional	Louvre
Weight (g)	632	Maximal working	+50° C
IP Rating	IP66/IP68	temperature	
IK rating	IK10	Minimal working temperature	-20° C
Finishing colour	White silk-screen	Maximal static load (kN)	5
Body material	Anodized aluminum	Walk-over	Yes
	anticorodal 6082	Driver-over	No
Diffuser material	Extraclear tempered glass	Maximal surface temperature	+50° C
Diffuser thickness (mm)	10	Areas EN 60598-2-13	A1 / A2
Class ISO 9223	CX		

Electrical data

Nominal power (W)	7	
Power supply (input power	Costant voltage - 24V	
type)		
Ballast	Remote	
Insulation class	111	
Dimmable	Yes	
Power cable type	H05RN - F 2x0,75 mm ²	
Power cable length	10 m	


Electrical connection	Parallel connection
Idroskud® protection	Yes
Inverse polarity protection	Yes
Voltage spikes protection	Yes




Photometry

150° 165° 160° 165° 150° 135° 165° 150° 135° 1500 135° 1500 1500 105° 105° 105° 105° 105° 105° 105° 105° 105° 105° 105° 105° 105° 105° 105° 105° 105°

Technical drawing





Accessories



DRAINING OUTERCASE Outercase draining VITRUM 3

Cod: VITZZZ002



SLIM DRAINING OUTERCASE Outercase slim VITRUM 3

Cod: VITZZZ005



PLASTERBOARD RING Plasterboard ring VITRUM 3

Cod: VITZZZ008



EXTRACTION KIT Suction cup for VITRUM 3

Cod: VITZZZ011